



**Features/Applications**

GREMSPOOL® is a range of heat shrink tubing available in a conveniently packaged dispenser. It is specially designed to meet the requirements of wholesalers, distributors repair shops or electrical work shops.

**GREMSPOOL® GMB**

Contains 2:1 ratio, 125°C, flexible, flame retardant irradiated polyolefin heat shrink tubing. Refer to GREMTUBE® G55 data sheet for details.

**GREMSPOOL® GMB A**

Contains 3:1 ratio, 110°C, flexible, flame retardant irradiated polyolefin heat shrink tubing with adhesive. Refer to GREMTUBE® G61A 3X data sheet for details.

**Various**

Standard colours :

- GREMSPOOL® GMB: Black, clear, red, blue, yellow, green, white, yellow/green.
- GREMSPOOL® GMB A: Black.

(others colours available on request)

**Dimensions**



Reference	As supplied (mm)	After recovery (mm)		Standard Dispenser Length (m)
	Inside Diameter Min. (D)	Inside Diameter Max. (d)	Wall Thickness Min. (t)	
GREMSPOOL® GMB				
001,6	1,6	0,8	0,36	15
002,4	2,4	1,2	0,43	15
003,2	3,2	1,6	0,43	15
004,8	4,8	2,4	0,43	12
006,4	6,4	3,2	0,56	12
009,5	9,5	4,8	0,56	8
012,7	12,7	6,4	0,56	8
019,1	19,1	9,5	0,69	5
025,4	25,4	12,7	0,76	5



Reference	As supplied (mm)	After recovery (mm)		Standard Dispenser Length (m)
	Inside Diameter Min. (D)	Inside Diameter Max. (d)	Total Wall Thickness Nom. (t)	
GREMSPOOL® GMB A				
003,0	3,0	1,0	1,00	4
006,0	6,0	2,0	1,20	4
009,0	9,0	3,0	1,30	3
012,0	12,0	4,0	1,35	3
019,0	19,0	6,0	2,00	2
024,0	24,0	8,0	2,20	2

•Special printing on box and special tubing are available on request.

Recommended storage conditions: Keep in cool, dry, ventilated storage (maximum temperature of 35°C) and in closed containers.



Whilst every attempt is made to provide data that is as accurate as possible the values provided should be treated as a guide only. It remains the responsibility of the user to test the product and determine suitability. GREMTEK shall not be held responsible for any loss or defect resulting from incorrect, improper or inappropriate use of this product.