



Features/Applications

GREMFLEX® GTU10J is a tubular fiberglass braided sleeve coated with a Polyurethane varnish. GREMFLEX® GTU10J offers a continuous working temperature of -30°C up to +155°C, an outstanding abrasion resistance and a good flexibility. GREMFLEX® GTU10J is suitable for electrical insulation and mechanical protection.

Various

Standard colours: Light brown , black, white, red, yellow, orange

Dimensions

Reference <i>GREMFLEX® GTU10J</i>	Recommended range of use (mm)	Wall thickness (mm)
000,5	0,5	0,50
001,0	1,0	0,50
001,5	1,5	0,50
002,0	2,0	0,50
003,0	3,0	0,50
004,0	4,0	0,50
005,0	5,0	0,50
006,0	6,0	0,50
007,0	7,0	0,50
008,0	8,0	0,73
009,0	9,0	0,73
010,0	10,0	0,73
012,0	12,0	0,73
014,0	14,0	0,78
016,0	16,0	0,78
018,0	18,0	0,78
020,0	20,0	0,78
022,0	22,0	1,03
025,0	25,0	1,03
030,0	30,0	1,50
032,0	32,0	1,75
035,0	35,0	1,75
040,0	40,0	1,75

Cutting

GREMFLEX® GTU10J can be cut to length.

Packaging

Available in spool, coils or cut pieces (on request). Other packaging or diameter available upon request.

Property	Values	Test Methods	
Physical	Working temperature	-30°C to +155°C	
	Short term temperature	+180°C	
	Thermal classification	Class 155 (Class F)	EN 60684
	Flammability	Combustible	-
Chemical	Fluid resistance	Good resistance to hydrocarbons, such as fuels, oils no dissolution	EN 60684
	Electrical	Dielectric strength	Up to 10 kV

